

# Magellan® 8400

Performance, Quality and Value



## Features:

- Enhanced All-Weights® Platter
- Aggressive and ergonomic 360° 5-sided scanning
- Multiple interface solution supports all popular host interfaces
- FirstStrike® advanced decoding software
- Flash memory for easy, low cost upgrades
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- GSI DataBar™ (RSS) decoding
- Optional EAS functionality
- Integrated Produce Lift Bar or Produce Rail™
- Value Added Features:
  - Host Download
  - Diagnostic Reporting
  - Productivity Index Reporting™ (PIR)
  - Cashier Training™



## Mechanical

### Length

Model	Scanner/Scale	Length
8401	Short scanner	14.0 in / 35.3 cm
8402	Medium scanner	15.8 in / 39.9 cm
8403	Long scanner	20.0 in / 50.8 cm
8404	Med. scanner/scale	15.8 in / 39.9 cm
8405	Long scanner/scale	20.0 in / 50.8 cm

**Width:** 11.5 in / 29.2 cm

**Depth (below counter):** 4.0 in / 10.0 cm

**Height (above counter):** 51 in / 131 cm

### Scale Capacities

**Capacity:** 300 lb / 15 kg

**Minimum Increment:** 0.01 lb / 0.005 kg

**Vibration Immunity:** 4 programmable filter settings

**Maximum Static Weight:** 150 lb / 68 kg

**Adjustments Required:** Calibration only

## Optical

**Scan Lines:** 52

**Motor Speed:** 6,000 rpm

**Scan Rate:** 5,200 lines/sec.

**Scan Zone:** 360°

**Sides Read:** 5

**Read Height:** 6.0 in / 15.2 cm

## Environmental

### Temperature Rating:

**Operating:** 50 to 104 °F / 10 to 40 °C

**Storage:** -40 to 158 °F / -40 to 70 °C

**Humidity:** 5 to 95% NC

## Decoding Capability

The Magellan® 8400 autodiscriminates between the following supported symbologies:

- UPC Versions A & E
- UPC Supplementals (Bookland & Coupon Code)
- UPC Add-ons (sub 2, sub 5 & C128)
- EAN 8, 13
- JAN 8, 13
- EAN/JAN two label
- UCC/EAN 128
- Code 39 (with full ASCII)
- Code 128
- Code 93
- Interleaved 2 of 5
- Italian Pharmacode
- Codabar/NW7
- MSI/Plessey
- GSI DataBar™ (RSS)

# Data Sheet

## Electrical

### AC Power requirements:

100-250 VAC, 50-60 Hz

7 Watts (nominal)

8 Watts (maximum)

4 Watts (sleep mode)

## Communications

**Host:** All Magellan® 8400 models support IBM 46XX, RS-232, OEM USB, Dual RS-232 scanner-scale, and Keyboard Wedge and USB for scanner only models.

### Other:

Powered RS-232 auxiliary port

Scale host port

Remote scale display port

EAS port

## Safety & Regulatory

**Electrical:** IRAM (Argentina), AS/NZS 60950 (Australia); CSA-C22.2 No. 60950 (Canada); EN60 950 (TÜV Europe); PSE Mark (Japan); UL 60950 (USA); BSMI Taiwan

**Emissions:** FCC part 15, Class A (USA); AS/NZS 3548 (Australia/New Zealand); EN 55022-B (Europe); CISPR 22-B, VCCI-B (Japan)

**Laser Safety:** Class IIa Laser Product

(CAUTION: Laser Light – do not stare into beam); IEC 825 Class 1, EN60 825 Class (Europe)

**Restriction of Hazardous Substances:** Complies to EU RoHS



**Weights and Measures:** Argentina; Australia; Brazil; Canada; 90/384/EEC (Europe); Mexico; New Zealand; USA (NIST Handbook 44)

**Contact your Datalogic Scanning representative** for certification schedule and additional listings.

## Other

**EAS Compatibility:** Integrated EAS hardware will work with Counterpoint IV, V, VI, and VII models available from Checkpoint® Systems. Sensormatic® compatible.

**Good Read** acknowledgement with Sensormatic® and Checkpoint® Systems.



# DATALOGIC™

**Datalogic Scanning, Inc.**

E-mail us at: [scanning@datalogic.com](mailto:scanning@datalogic.com)

[www.scanning.datalogic.com](http://www.scanning.datalogic.com)



Copyright © Datalogic Scanning, Inc. 2007/2008. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc. • Datalogic Scanning, Inc. of Eugene, Oregon, USA is ISO registered by NQA. • Datalogic is a registered trademark of Datalogic S.p.A. in many countries and the Datalogic logo is a trademark of Datalogic S.p.A. • Magellan, All Weights and FirstStrike are registered trademarks of Datalogic Scanning Inc. • OmegaTek, Productivity Index Reporting (PIR), Produce Rail and Cashier Training are trademarks of Datalogic Scanning Inc. • All other brand and product names are trademarks of their respective owners. • Additional information concerning this product or other Datalogic products and services can be found at the Datalogic web site: [www.scanning.datalogic.com](http://www.scanning.datalogic.com). • Product specifications are subject to change without notice.