

Magellan® 8500

With OmegaTek™ Productivity Technology

Data Sheet



Features:

- OmegaTek™ Productivity Technology
- SurroundScan® 3D Scanning™ Technology
- Enhanced All-Weights® Platter
- FirstStrike™ Advanced Decoding Software
- Multiple interface solution supports all popular host interfaces
- Flash memory for easy, low cost upgrades
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- Optional EAS functionality
- Sunrise 2005 and GTIN compliant
- Value Added Features:
 - Host Download
 - Diagnostic Reporting
 - Productivity Index Reporting™ (PIR)
 - Cashier Training™



Mechanical

Dimensions

Length:

- Model 8500 (short scanner): 16.5 in / 41.9 cm
- Model 8501 (long scanner): 20.0 in / 50.8 cm
- Model 8502 (long scanner/scale): 20.0 in / 50.8 cm

Width: 11.5 in / 29.2 cm

Depth (below counter): 5.0 in / 12.7 cm

Height (above counter): 7.0 in / 17.8 cm

Weight

- Model 8500 (short scanner): 18.0 lb / 8.2 kg
- Model 8501 (long scanner): 20.0 lb / 9.1 kg
- Model 8502 (long scanner/scale): 26.0 lb / 11.8 kg

Scale Capacities

Capacity: 30.0 lb / 15 kg

Minimum Increment: .01 lb / 0.005 kg

Vibration Immunity: 4 programmable filter settings

Maximum Static weight: 150 lb / 68 kg

Adjustments Required: Calibration only

Optical

Scan Lines: 64

Motor Speed: 6,000 rpm

Scan Rate: 6,400 lines/sec.

Scan Zone: 360° x 2

Sides Read: 6

Read Height: 6.0 in / 15.2 cm

Decoding Capability

The Magellan® 8500 decodes and autodiscriminates all of the following symbologies:

- UPC Versions A & E
- UPC Supplementals (Bookland & Coupon Code)
- UPC Add-ons (sub 2 or P2, sub 5 or P5 & CI28)
- GSI DataBar™ (Omnidirectional, Expanded and Stacked)
- EAN 8, 13
- JAN 8, 13
- EAN/JAN two label
- UCC/EAN 128
- Code 39 (with full ASCII)
- Code 128
- Code 93
- Interleaved 2 of 5
- Italian Pharmacode
- Codabar/NW7
- MSI/Plessey

Environmental

Temperature Rating

Operating: 50 to 104 °F / 10 to 40 °C

Storage/Transport: -40 to 158 °F / -40 to 70 °C

Humidity: 5 to 95% NC

Electrical

AC Power Requirements: 100-250 VAC, 50-60 Hz; 9 Watts (nominal), 17 Watts (maximum), 4 Watts (sleep mode)

Communications

Host: All Magellan® 8500 models support –IBM 46XX, RS-232, IBM USB, and Keyboard Wedge (scanner only)


Other: RS-232 handheld scanner port; scale host port; remote scale display port; EAS interlock port

Safety & Regulatory

Electrical: UL 60950; CSA-C22.2 no.60950; EN60950; BSMI Taiwan

Emissions: FCC part 15 subpart j, Class B (USA); AS/NZS 3548 (Australia/New Zealand); ICES-0003 (Canada); VCCI; EN 55022; CISPR 22 and others.

Laser Safety: Class IIa Laser Product; IEC 60825 Class 1

 (CAUTION: Laser Light – do not stare into beam)

Restriction of Hazardous Substances: Complies to EU RoHS



Weights & Measures: *Standards - HB44, OIML R76-1 and R76-2, EN45501, 90/384/EEC, NOM, and others.

*Countries approved: USA, Canada, Mexico, Europe,

Australia, New Zealand, Puerto Rico, and most of the world.

*Contact your Datalogic Scanning representative for certification schedule and additional listings.

Other

EAS Compatibility: Integrated EAS hardware will work with Counterpoint IV, V, VI, and VII models available from Checkpoint Systems.

Good read acknowledgement with Sensormatic.

DATALOGIC™

Datalogic Scanning, Inc.

E-mail us at: scanning@datalogic.com

www.scanning.datalogic.com



Copyright © Datalogic Scanning, Inc. 2005-2008. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc. • Datalogic Scanning, Inc. of Eugene, Oregon, USA is ISO registered by NQA. • The Datalogic logo is a trademark of Datalogic S.p.A. • Magellan, All Weights®, SurroundScan and FirstStrike are registered trademarks of Datalogic Scanning Inc. • OmegaTek, 3D Scanning, Productivity Index Reporting (PIR), and Cashier Training are trademarks of Datalogic Scanning Inc. • All other brand and product names are trademarks of their respective owners. • Additional information concerning this product or other Datalogic products and services can be found at the Datalogic web site: www.scanning.datalogic.com. • Product specifications are subject to change without notice.

R40-0072-US H 0508